

1kV heat shrinkable busbar protection casing

Product legend



Technical Data

Specification	Applicable busbar width	Internal diameter	Wall thickness	Internal diameter	Wall thickness	Standard packaging (m/disc)	Application (mm)
1kV MPG 30	20-30	30.2±0.8	0.45±0.15	14.7±1.0	0.9±0.2	50	16-29
1kV MPG 35	30-40	35.2±0.8	0.50±0.15	17.3±1.0	1.0±0.2	50	18-34
1kV MPG 40	40-50	40.0±1.0	0.50±0.15	19.8±1.0	1.0±0.2	50	21-39
1kV MPG 50	50-60	50.0±1.0	0.50±0.15	24.8±1.0	1.0±0.23	50	26-49
1kV MPG 60	60-70	60.0±1.0	0.65±0.15	29.8±1.0	1.1±0.2	25	35-55
1kV MPG 70	80-90	70.0±1.0	0.65±0.15	34.0±2.0	1.1±0.2	25	40-65
1kV MPG 80	90-100	80.0±1.0	0.65±0.20	39.0±2.0	1.2±0.2	25	45-75
1kV MPG 90	120	90.0±1.0	0.65±0.20	44.0±2.0	1.2±0.2	25	50-88
1kV MPG 100	140	100.0±2.0	0.65±0.20	49.0±2.0	1.3±0.2	25	55-95
1kV MPG 120	180	120.0±2.0	0.80±0.20	59.0±2.0	1.4±0.2	25	65-115
1kV MPG 150	240	150.0±2.0	0.80±0.20	74.0±2.0	1.4±0.2	25	80-145