

## XL-3 Series Flame-Retardant Thin-Wall Thermal Shrinkable Bushing

### Product legend



#### Application:

XL-3 series flame-retardant thin-wall thermal shrinkable bushing is characterized by thin wall, good insulation, low shrinking temperature, fast shrinking, softness, and it is specially applicable to the protection of temperature sen-sitive components.

Shrinking ratio:2:1

Initial shrinking temperature:80℃

Color: Black, red, blue, white, yellow, green, and transparent.(Other colors are also available)

Rated voltage:300v

## Technical Data

Specification (mm)	Dimension before shrinking		Dimension after shrinking		Standard packaging (m/disc)	Application (mm)
	Internal diameter	Wall thickness	Internal diameter	Wall thickness		
φ 1.0	1.2±0.3	0.10±0.05	0.6	0.20±0.05	200	0.65-0.9
φ 1.5	1.7±0.3	0.10±0.05	0.8	0.20±0.05	200	0.9-1.4
φ 2.0	2.2±0.3	0.13±0.05	1.0	0.22±0.05	200	1.5-1.8
φ 2.5	2.6±0.3	0.13±0.05	1.3	0.25±0.05	200	1.5-2.3
φ 3.0	3.2±0.4	0.13±0.05	1.5	0.28±0.05	200	1.75-2.7
φ 3.5	3.6±0.4	0.13±0.05	1.8	0.28±0.05	200	2-3.2
φ 4.0	4.2±0.4	0.15±0.05	2.0	0.30±0.05	200	2.5-3.6
φ 5.0	5.2±0.4	0.15±0.05	2.5	0.32±0.05	200	3-4.5
φ 6.0	6.2±0.4	0.15±0.05	3.0	0.32±0.05	200	3.5-5.4
φ 7.0	7.2±0.4	0.15±0.05	3.5	0.32±0.08	100	4-6.3
φ 8.0	8.2±0.5	0.15±0.05	4.0	0.32±0.05	100	4.5-7.2
φ 9.0	9.2±0.5	0.16±0.05	4.5	0.35±0.08	100	5-8
φ 10	10.2±0.5	0.16±0.05	5.0	0.35±0.08	100	5.5-9
φ 11	11.2±0.5	0.18±0.05	5.5	0.40±0.08	100	6-10
φ 12	12.2±0.5	0.20±0.05	6.0	0.40±0.08	100	6.5-11
φ 13	13.2±0.5	0.20±0.05	6.5	0.40±0.08	100	7-12
φ 14	14.2±0.5	0.20±0.05	7.0	0.40±0.08	100	7.5-13
φ 15	15.2±0.5	0.20±0.05	7.5	0.40±0.08	100	8-14.8
φ 16	16.2±0.5	0.20±0.05	8.0	0.40±0.08	100	9-15.8